

Material Safety Data Sheet

Product Number: 7453

Date Prepared: November 2009

Revision Date: June 2013

SECTION 1: Manufacturer Identification

Mason Color Works, Inc.
250 East 2nd Street/P.O. Box 76
East Liverpool, OH 43920-5076

Phone: (330) 385-4400

Fax: (330) 385-4488

HMIS Classification:

Health	2*
Flammability	0
Reactivity	0
Personal Protection	See Section 6

*Indicates possible chronic health effects.

SECTION 2: Identification of Product

Chemical Family: Inorganic
Product Names: 7453
Chemical Abstract Number(CAS): 8007-18-9
Chemical Name: Nickel Antimony Titanium Yellow
Chemical Formula: (Ti,Ni,Sb)O₂

SECTION 3 & 4: Hazardous ingredients Identity/Information and Overexposure Symptoms

	ACGIH-TLVs	OSHA PELs	NOISHA RELs
Titanium Dioxide (TiO₂)	10 mg/m ³	10 mg/m ³ (total)	0.2 mg/m ³
Cas # 1309-37-1		5 mg/m ³ (respirable)	

SYMPTOMS OF OVEREXPOSURE:

Inhalation: Inhalation of dust can cause irritation of the nose, throat, and lungs.

Eye Contact: Like any foreign body, particles can cause mechanical irritation.

Skin Contact: This material can cause irritation if not promptly washed from skin.

Ingestion: This material is not expected to produce adverse effects.

	ACGIH-TLVs	OSHA PELs	NOISHA RELs
Antimony Trioxide (Sb₂O₃)	0.5 mg/m ³	0.05 mg/m ³	0.05 mg/m ³
Cas # 1309-64-4			

SYMPTOMS OF OVEREXPOSURE:

Inhalation: Prolonged excessive absorption in sufficient quantities may produce gastrointestinal upset, nervous complaints, inflammation of mucus membrane of the nose and throat, metallic taste and stomatitis.

Eye Contact: May cause irritation.

Skin Contact: May cause irritation.

Ingestion: Prolonged ingestion may cause gastrointestinal upset.

	ACGIH-TLVs	OSHA PELs	NOISHA RELs
Nickel Oxide (NiO)	0.2 mg/m ³	1 mg/m ³	0.015 mg/m ³
Cas # 7440-02-0			

ACGIH: Inhalable fraction, the concentration of inhalable particulate for application of this TLV is to be determined from the fraction passing a size-selector with characteristics defined in (A1). (A1) - Confirmed human carcinogen: Agent is carcinogenic to humans based on epidemiologic studies of, or convincing clinical evidence, in exposed humans. (Ca) Carcinogen.

SYMPTOMS OF OVEREXPOSURE:

Inhalation: Primary enters through inhalation of dust.

Eye Contact: May cause irritation in eyes and mucous membranes.

Skin contact: may irritate skin, can cause "Nickel Itch" in sensitive persons.

Ingestion: Low order of acute toxicity. May cause gastro-intestinal disorders.

SECTION 5: Emergency and First Aid Procedures

Eye: flush thoroughly with water for 15 minutes.

Skin: remove contaminated clothing, wash thoroughly with soap and water.

Inhalation: remove to fresh air, may give oxygen if needed.

Ingestion: give large amounts of water to induce vomiting, only in conscious persons.

IF THESE FIRST AID MEASURES FAIL, CONSULT A PHYSICIAN

Principal Routes of Entry:

Inhalation: Dust from this product may cause irritation of the respiratory system.

Overexposure may cause lung damage.

Ingestion: Large amounts may cause irritation of the gastrointestinal tract, nausea, vomiting and diarrhea.

Skin & Eye: Nuisance dust, prolonged or repeated may cause irritation.

SECTION 6: Special Protection Information

Respiratory Protection: Use only NIOSHA/OSHA approved respiratory protection with adequate ventilation; avoid breathing dust. Do not exceed Occupational Exposure Limit. Wash thoroughly after handling. No food or beverage should be consumed in work area.

Personal Protective Equip: Wear appropriate gloves and goggles to avoid skin and eye contact. Safety showers and eye stations must be present in work stations.

Ventilation: Use local exhaust or mechanical such as a dust collector to maintain dust levels below Occupational Exposure Limits.

SECTION 7: Physical and Chemical Characteristics

Boiling Point: N/A

Solubility in water: trace

Vapor Pressure (mmHg): N/A

Vapor Density (air=1): N/A

Appearance:

Odor: Odorless

Specific Gravity (water=1): N/A

Evaporation rate: None

% Volatile by volume: None

SECTION 8: Reactivity Data

Stability: Stable
Hazardous Polymerization: will not occur
Incompatibility: None
Hazard Decomposition of product: N/A

SECTION 9: Fire and Explosive Data

Flash point: N/A Flammable Limits:
Unusual Fire and Explosion Hazard: None expected.
Extinguishing Media: Carbon Dioxide, dry chemical or water
Special Fire Fighting Procedures: Wear self contained breathing apparatus when large quantities involved.

SECTION 10: Spill or Leak Procedures

Contain spillage and scoop or vacuum. Avoid making dust, put in appropriate container for disposal. Waste disposal method in accordance with Federal, State and Local Laws.

This product is a blend of various metal oxides, salts and some compounds which are interfused by high calcinations to form the finished product. Section 3, Hazardous ingredients Identity/Information, and Section 4, Symptoms of Overexposure, pertain to individual components. Section 5 through Section 10 are in reference to the finished product.

***** Attention all Retailers of Mason Stains *****

ALL retailers of this product are REQUIRED by law to supply their customers with a copy of material safety data sheet with initial purchase.

*****SARA 313**

This product contains certain oxides and compounds which are subject to reporting requirements of Superfund Amendment and Reauthorization Act (**SARA**) of 1986, Section 313 of the Emergency Planning and Community Right to Know Act and of 40 CFR, Part 372.

The information contained in this MSDS must be provided to every employee who is exposed to this product in any way. We recommend the user reads and understands the contents herein before using this material.

PLEASE KEEP ON FILE FOR FUTURE REFERENCE. DO NOT THROW AWAY! MSDS'S ARE REQUIRED FOR FIRST SHIPMENT, AND WILL BE SENT AGAIN WHEN REVISED UPON YOUR NEXT ORDER OF PRODUCT

OR BY REQUEST.

disclaimer