# Safety Data Sheet

DATE PREPARED 4/28/2015

6374 ZIRCONIUM VANADIUM BLUE ZIRCON HMIS Classification: Н

Health	2*
Flammability	0
Reactivity	0
Personal Protection	See Section 8



MANUFACTURERS OF CERAMIC COLORS

!

### 1.1 Product identifier

Product name



### ZIRCONIUM VANADIUM BLUE ZIRCON

Zirconium Vanadium Blue Zircon, an inorganic pigment, is a reaction product of high temperature calcination in which Zirconium (IV) Oxide, Silicon (IV) Oxide, and Vanadium (IV) Oxide in varying amounts are homogeneously and ionically interdiffused to form a crystalline matrix of zircon Its composition may include any one or a combination of the modifiers alkali or alkaline earth halides

Product number	6374 DARK TURQUOISE
EC no.	269-057-9
CAS no.	68186-95-8
Index no.	C.I. 77998

#### 1.4 Supplier's details

Name Address	Mason Color Works Inc. 250 East Second Street East Livepool, Ohio 43920
	USA
Telephone	330 385 4400
Fax	330 385 4488

# **SECTION 2: Hazard identification**

Classification of the substance or mixture		
GHS classification in accordance with OSHA (29 CFR 1910.1200)	Not a hazardous substance or mixture.	
GHS label elements, including precautionary statements	Not a hazardous substance or mixture.	

Other hazards which do not result in classification

## **SECTION 3: Composition/information on ingredients**

6374	ZIRCONIUM VANAD	IUM BLUE ZIRCON	C.I. Pigment Blue 71	100%
	EC no.	269-057-9		
	CAS no.	68186-95-8		
	Index no.	C.I. 77998		
	Formula	(Zr,V)SiO4		
SECTION	4: First-aid measure	es		
•Contact w	vith skin:	Wash with plenty of	water and soap.	
•Contact w	vith eyes:	Wash immediately v	vith water for at least 10 minutes.	
•Swallowi	ng:	Induce vomiting. SEE	Induce vomiting. SEEK A MEDICAL EXAMINATION IMMEDIATELY and present the safety-data sheet.	
		A suspension of activ	A suspension of activated charcoal in water, or liquid paraffin may be administered.	
<ul> <li>Inhalation</li> </ul>	on:	Ventilate the premis	es.	
		The patient is to be r	emoved immediately from the contamin	nated premises and made to rest in a well ventilated area.
		Should the patient fe	el unwell, OBTAIN MEDICAL ATTENTION	

Not a hazardous substance or mixture.

# **SECTION 5: Fire-fighting measures**

<ul> <li>Recommended extinguishers:</li> </ul>	Water, CO2, Foam, Chemical powders, according to the materials involved in the fire.
•Extinguishers not to be used:	None in particular.
<ul> <li>Risks arising from combustion:</li> </ul>	Avoid inhaling the fumes.
•Protective equipment:	Use protection for the respiratory tract.

# **SECTION 6: Accidental release measures**

<ul> <li>Measures for personal safety:</li> </ul>	Use gloves and protective clothing. In the event of particulates aerosols use respiratory protection.
•Environmental measures: .	Keep away from drains, surface- and ground-water and soil
•Cleaning methods:	Limit leakages with earth or sand. If the product has escaped into a water
	course, into the drainage system, or has contaminated the ground or vegetation, notify the competent authorities.
	Remove the waste materials with a suitable device (for instance a suction pump) and dispose.
	After the product has been recovered, rinse the area and materials involved with water.
SECTION 7: Handling and storage	
•Handling precautions:	Wear suitable gloves, glasses and face protection. Avoid contact and inhalation of the vapours/powders.
	Do not eat or drink while working.
<ul> <li>Incompatible materials:</li> </ul>	None in particular.
•Chavage conditions	

•Storage conditions:	Always keep the containers tightly closed.
<ul> <li>Instructions as regards storage premises:</li> </ul>	Adequately ventilated premises.

# SECTION 8: Exposure controls / personal protection

Zirconium Compounds (as Zr)	ACGIH-TLVs 10 mg/m <sup>3</sup> (total)	OSHA PELs 15 mg/m <sup>3</sup> (total)	NOISHA RELs 5 mg/m <sup>3</sup>
	5 mg/m <sup>3</sup> (Respirable)	5 mg/m <sup>3</sup> (respirable)	15 min. C
Silica, Crystalline (SiO2)	0.1 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>	0.05 mg/m <sup>3</sup>
Vanadium Fume (as V <sub>2</sub> O <sub>5</sub> )	0.05 mg/m <sup>3</sup>	0.05 mg/m <sup>3</sup>	0.05 mg/m <sup>3</sup>

<ul> <li>Precautionary measures:</li> </ul>	Give adequate ventilation to the premises where the product is stored and/or handled.
<ul> <li>Respiratory protection:</li> </ul>	Use suitable respiratory protection.
<ul> <li>Protection for hands:</li> </ul>	Not needed for normal use.
•Eye protection:	Not needed for normal use.
•Protection for skin:	No special precaution must be adopted for normal use.

# SECTION 9: Physical and chemical properties

Appearance/form	Lt Blue/Powder
Odor	None
SPECIFIC GRAVITY	4.63
рН	5.2
Melting point/freezing point	>1000c
Initial boiling point and boiling range	NA
Flash point	NA
Evaporation rate	NA
Flammability (solid, gas)	none
Upper/lower flammability limits	NA
Upper/lower explosive limits	NA
Vapor pressure	NA
Vapor density	NA
Relative density	NA
Solubility(ies)	insoluble
Partition coefficient: n-octanol/water	NA
Auto-ignition temperature	NA
Decomposition temperature	NA
Viscosity	NA
Explosive properties	none
Oxidizing properties	none

# **SECTION 10: Stability and reactivity**

Chemical stability	STABLE
Possibility of hazardous reactions	WILL NOT OCCUR
Incompatible materials	NONE
Hazardous decomposition products	N/A

# **SECTION 11: Toxicological information**

ORAL	LD50 (male and female rats) > 2200 mg/kg bw
INHALATION	LC50 (male and female rats; 4 hours) > 5.1 mg/L
SKIN	N/A
NON IRRITATING TO THE SKIN	
NON IRRITATING TO THE EYES	

THIS PIGMENT IS NOT LISTED IN THE NATIONAL TOXICOLOGY PROGRAM (NTP) REPORT ON CARCINOGENS. IT IS NOT LISTED AS A POTENTIAL CARCINOGEN IN THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER(IARC) MONOGRAPHS. IT IS NOT FOUND TO BE A CARCINOGEN BY THE OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION(OSHA)

## **SECTION 12: Ecological information**

ECOTOXICITY	NO DATA
DEGRADABILITY	NO DATA
MOBILITY	NO DATA
BIOACCUMULATIVE	NO DATA

### **SECTION 13: Disposal considerations**

Disposal of the product	Contain spillage and scoop or vacuum. Avoid making dust put in appropriate container for disposal. Waste disposal method in accordance with Federal, State and Local Laws.
Disposal of contaminated packaging	Dispose of as unused product.
Waste treatment	MUST BE PROCESSED THROUGH IN-HOUSE TREATMENT
Sewage disposal	AVOID CITY DRAINS

## SECTION 14: Transport information

14.1 UN Number	None
14.2 UN Proper Shipping Name	None
14.3 Transport hazard class(es)	None
14.4 Packing group	None
14.5 Environmental hazards	None
14.6 Special precautions for user	None
14.7 Transport in bulk according to Annex II of	None
MARPOL 73/78 and the IBC Code	

### **SECTION 15: Regulatory information**

### Attention all Retailers of Mason Stains

ALL retailers of this product are REQUIRED by law to supply their customers with a copy of material safety data sheet with initial purchase.

\*\*\*SARA 313

This product contains certain oxides and compounds which are subject to reporting requirements of Superfund Amendment and Reauthorization Act (SARA) of 1986, Section 313 of the Emergency Planning and Community Right to Know Act and of 40 CRF, Part 372.

The information contained in this SDS must be provided to every employee who is exposed to this product in any way. We recommend the user reads and understands the contents herein before using this material.

PLEASE KEEP ON FILE FOR FUTURE REFERENCE. DO NOT THROW AWAY! SDS'S ARE REQUIRED FOR FIRST SHIPMENT, AND WILL BE SENT AGAIN WHEN REVISED UPON YOUR NEXT ORDER OF PRODUCT OR BY REQUEST.

Disclamer

### SECTION 16: REFERENCE INFORMATION

CPMA CLASSIFICATION AND CHEMICAL DESCRIPTIONS OF THE COMPLEX INORGANIC COLOR PIGMENTS Fourth Edition - January 2013 Update

https://www.osha.gov/index.html

http://chem.sis.nlm.nih.gov/chemidplus

13th Report on Carcinogens on October 2, 2014. http://monographs.iarc.fr/ENG/Classification/index.php