# **Safety Data Sheet**

**DATE PREPARED: 5/20/2015 SECTION 1: Identification** 

> 6385 RED MIXTURE

HMIS Classification:

Health 2\* 0 Flammability Reactivity 0

Personal Protection See Section 8

> **Product number 6385 PANSY PURPLE**

1.4 Supplier's details

Name Mason Color Works Inc. Address 250 East Second Street East Livepool, Ohio 43920

Telephone 330 385 4400 330 385 4488 Fax

**SECTION 2: Hazard identification** 

Classification of the substance or mixture

GHS classification in accordance with OSHA (29 (Not a hazardous substance or mixture.

GHS label elements, including precautionary stal Not a hazardous substance or mixture.

Other hazards which do not result in classificatic Not a hazardous substance or mixture.

## **SECTION 3: Composition/information on ingredients**

|      |                              | 70 | EC no.    | CAS no.    | index no.  | Formula            |                       |
|------|------------------------------|----|-----------|------------|------------|--------------------|-----------------------|
| 6003 | CHROME TIN PINK SPHENE       | 89 | 269-073-6 | 68187-12-2 | C.I. 77301 | CaO:SnO:SiO2:Cr2O3 | C.I. Pigment Red 233  |
| 6388 | COBALT SILICATE BLUE OLIVINE | 11 | 269-093-5 | 68187-40-6 | C.I. 77364 | Co2SiO4            | C. I. Pigment Blue 73 |

**SECTION 4: First-aid measures** 

•Contact with skin: Wash with plenty of water and soap.

•Contact with eyes: Wash immediately with water for at least 10 minutes.

•Swallowing: Induce vomiting. SEEK A MEDICAL EXAMINATION IMMEDIATELY and present the safety-data sheet.

A suspension of activated charcoal in water, or liquid paraffin may be administered.

•Inhalation: Ventilate the premises.

The patient is to be removed immediately from the contaminated premises and made to rest in a well ventilated area.

Should the patient feel unwell, OBTAIN MEDICAL ATTENTION

**SECTION 5: Fire-fighting measures** 

•Recommended extinguishers: Water, CO2, Foam, Chemical powders, according to the materials involved in the fire.

•Extinguishers not to be used: None in particular. •Risks arising from combustion: Avoid inhaling the fumes.

•Protective equipment: Use protection for the respiratory tract.



MANUFACTURERS OF CERAMIC COLORS

#### **SECTION 6: Accidental release measures**

• Measures for personal safety: Use gloves and protective clothing. In the event of particulates aerosols use respiratory protection.

• Environmental measures: . Keep away from drains, surface- and ground-water and soil

•Cleaning methods: Limit leakages with earth or sand. If the product has escaped into a water

course, into the drainage system, or has contaminated the ground or vegetation, notify the competent authorities.

Remove the waste materials with a suitable device (for instance a suction pump) and dispose.

After the product has been recovered, rinse the area and materials involved with water.

**SECTION 7: Handling and storage** 

• Handling precautions: Wear suitable gloves, glasses and face protection. Avoid contact and inhalation of the vapours/powders.

Do not eat or drink while working.

•Incompatible materials: None in particular.

•Storage conditions: Always keep the containers tightly closed.

•Instructions as regards storage premises: Adequately ventilated premises.

## SECTION 8: Exposure controls / personal protection

|                                    | ACGIH-TLVs             | OSHA PELs             | NOISHA RELs            |
|------------------------------------|------------------------|-----------------------|------------------------|
| Tin Oxide (as Sn) (Total Dust)     | 2.0 mg/m <sup>3</sup>  | 2.0 mg/m <sup>3</sup> | 2.0 mg/m <sup>3</sup>  |
| Chromium (III) Compounds (as Cr)   | 0.5 mg/m <sup>3</sup>  | 0.5 mg/m <sup>3</sup> | 0.5 mg/m <sup>3</sup>  |
| Cobalt, Metal, Dust & Fume (as Co) | 0.02 mg/m <sup>3</sup> | 0.5 mg/m <sup>3</sup> | N/A                    |
| Silica, Crystalline (SiO2)         | 0.1 mg/m <sup>3</sup>  | 10 mg/m <sup>3</sup>  | 0.05 mg/m <sup>3</sup> |

## Respiratory protection:

Suitable respiratory protection for higher concentrations or long-term effect: Particle filter EN 143 Type

P1, low efficiency, (solid particles of inert substances).

Hand protection:

Chemical resistant protective gloves (EN 374)

e.g. nitrile rubber (0.4 mm), chloroprene rubber (0.5 mm), polyvinylchloride (0.7 mm) and other

Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection:

Safety glasses with side-shields (frame goggles) (EN 166)

General safety and hygiene measures:

Handle in accordance with good industrial hygiene and safety practice. Due to the colouring properties of the product closed work clothes should be used, to avoid stains during manipulation. Hands and/or face should be washed before breaks and at the end of the shift.

#### **SECTION 9: Physical and chemical properties**

| Appearance/form                         | RED/POWDER |
|---|------------|
| Odor                                    | None       |
| SPECIFIC GRAVITY                        | 4.96       |
| рН                                      | 6          |
| Melting point/freezing point            | <1000 C    |
| Initial boiling point and boiling range | NA         |
| Flash point                             | NA         |
| Evaporation rate                        | NA         |
| Flammability (solid, gas)               | none       |
| Upper/lower flammability limits         | NA         |
| Upper/lower explosive limits            | NA         |
| Vapor pressure                          | NA         |
| Vapor density                           | NA         |
| Relative density                        | NA         |
| Solubility(ies)                         | insoluble  |
| Partition coefficient: n-octanol/water  | NA         |
| Auto-ignition temperature               | NA         |
| Decomposition temperature               | NA         |
| Viscosity                               | NA         |
| Explosive properties                    | none       |
| Oxidizing properties                    | none       |
|   |            |

## **SECTION 10: Stability and reactivity**

Chemical stability STABLE

Possibility of hazardous reactions WILL NOT OCCUR

Incompatible materials NONE

Hazardous decomposition products N/A

## **SECTION 11: Toxicological information**

ORAL LD50 (male and female rats) > 2200 mg/kg INHALATION LC50 (male and female rats; 4 hours) > 5.4 mg/L

SKIN UNKNOWN

NON IRRITATING TO THE SKIN NON IRRITATING TO THE EYES

THIS PIGMENT IS NOT LISTED IN THE NATIONAL TOXICOLOGY PROGRAM (NTP) REPORT ON CARCINOGENS.

IT IS NOT LISTED AS A POTENTIAL CARCINOGEN IN THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER(IARC) MONOGRAPHS.

IT IS NOT FOUND TO BE A CARCINOGEN BY THE OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION(OSHA)

## **SECTION 12: Ecological information**

ECOTOXICITY NO DATA
DEGRADABILITY NO DATA
MOBILITY NO DATA
BIOACCUMULATIVE NO DATA

### **SECTION 13: Disposal considerations**

**Disposal of the product**Contain spillage and scoop or vacuum. Avoid making dust

put in appropriate container for disposal. Waste disposal method in accordance with

Federal, State and Local Laws.

Disposal of contaminated packaging Dispose of as unused product.

Waste treatment MUST BE PROCESSED THROUGH IN-HOUSE TREATMENT

Sewage disposal AVOID CITY DRAINS

## **SECTION 14: Transport information**

14.1 UN Number None
14.2 UN Proper Shipping Name None
14.3 Transport hazard class(es) None
14.4 Packing group None
14.5 Environmental hazards None
14.6 Special precautions for user None
14.7 Transport in bulk according to Annex II of None
MARPOL 73/78 and the IBC Code

# **SECTION 15: Regulatory information**

#### **Attention all Retailers of Mason Stains**

ALL retailers of this product are REQUIRED by law to supply their customers with a copy of material safety data sheet with initial purchase.

#### \*\*\*SARA 313

This product contains certain oxides and compounds which are subject to reporting requirements of Superfund Amendment and Reauthorization Act (SARA) of 1986, Section 313 of the Emergency Planning and Community Right to Know Act and of 40 CRF, Part 372.

The information contained in this MSDS must be provided to every employee who is exposed to this product in any way. We recommend the user reads and understands the contents herein before using this material.

PLEASE KEEP ON FILE FOR FUTURE REFERENCE. DO NOT THROW AWAY! MSDS'S ARE REQUIRED FOR FIRST SHIPMENT, AND WILL BE SENT AGAIN WHEN REVISED UPON YOUR NEXT ORDER OF PRODUCT OR BY REQUEST.

**Disclamer** 

#### **SECTION 16: REFERENCE INFORMATION**

CPMA CLASSIFICATION AND CHEMICAL DESCRIPTIONS OF THE COMPLEX INORGANIC COLOR PIGMENTS Fourth Edition - January 2013 Update

https://www.osha.gov/index.html

http://chem.sis.nlm.nih.gov/chemidplus

13th Report on Carcinogens on October 2, 2014. http://monographs.iarc.fr/ENG/Classification/index.php