Safety Data Sheet

DATE PREPARED 5 /6 /2015

UPDATED 6/15/2016

7453 NICKEL ANTIMONY TITANIUM YELLOW RUTILE

HMIS Classification:

Health 2* Flammability 0 Reactivity 0

Personal Protection See Section 8



1.1 Product identifier

Product name NICKEL ANTIMONY TITANIUM YELLOW RUTILE

Nickel Antimony Titanium Yellow Rutile, an inorganic pigment, is a reaction product of high temperature calcination in which Titanium (IV) Oxide, Nickel (II) Oxide, and Antimony (V) Oxide in varying amounts are homogeneously and ionically interdiffused to form a crystalline matrix of rutile.

Its composition may include any one or a combination of the modifiers CdO, Cr203, or Li2O

 Product number
 7453 YELLOW

 EC no.
 232-353-3

 CAS no.
 8007-18-9

 Index no.
 C.I. 77788

1.4 Supplier's details

Name Mason Color Works Inc.

Address 250 East Second Street

East Livepool, Ohio 43920

USA

 Telephone
 330 385 4400

 Fax
 330 385 4488

SECTION 2: Hazard identification

Signal Word: WARNING

GHS classification in accordance with OSHA (29 CFR 1910.1200)

H303: May be harmful if swallowed H313: May be harmful in contact with skin H317: May cause an allergic skin reaction

H333: May be harmful if inhaled H335: May cause respiratory

Not a hazardous substance
P261: Avoid breathing dust.
P262: Do not get in eyes, on skin.

P264: Wash hands thoroughly after handling.

SECTION 3: Composition/information on ingredients

NICKEL ANTIMONY TITANIUM YELLOW RUTILE

C.I. Pigment Yellow 53 100%

 EC no.
 232-353-3

 CAS no.
 68186-90-3

 Index no.
 C.I. 77310

 Formula
 (Ti,Ni,Sb)O2

SECTION 4: First-aid measures

•Contact with skin: Wash with plenty of water and soap.

•Contact with eyes: Wash immediately with water for at least 10 minutes.

• Swallowing: SEEK A MEDICAL EXAMINATION IMMEDIATELY and present the safety-data sheet.

A suspension of activated charcoal in water, or liquid paraffin may be administered.

•Inhalation: Ventilate the premises.

The patient is to be removed immediately from the contaminated premises and made to rest in a well ventilated area.

Should the patient feel unwell, OBTAIN MEDICAL ATTENTION

SECTION 5: Fire-fighting measures

•Recommended extinguishers: Water, CO2, Foam, Chemical powders, according to the materials involved in the fire.

•Extinguishers not to be used: None in particular. •Risks arising from combustion: Avoid inhaling the fumes.

•Protective equipment: Use protection for the respiratory tract.

SECTION 6: Accidental release measures

•Measures for personal safety: Use gloves and protective clothing. In the event of particulates aerosols use respiratory protection.

• Environmental measures: . Keep away from drains, surface- and ground-water and soil

•Cleaning methods: Limit leakages with earth or sand. If the product has escaped into a water

course, into the drainage system, or has contaminated the ground or vegetation, notify the competent authorities.

OSHA PELs

NOISHA REI

Remove the waste materials with a suitable device (for instance a suction pump) and dispose. After the product has been recovered, rinse the area and materials involved with water.

ACGIH-TLVs

SECTION 7: Handling and storage

Handling precautions: Wear suitable gloves, glasses and face protection. Avoid contact and inhalation of the vapours/powders.

Do not eat or drink while working.

•Incompatible materials: None in particular.

•Storage conditions: Always keep the containers tightly closed.

•Instructions as regards storage premises: Adequately ventilated premises.

SECTION 8: Exposure controls / personal protection

Titanium Dioxide (Total Dust) 10 mg/m³ 10 mg/m³ (total) 0.2 mg/m³ Antimony and Compounds (as Sb) 0.5 mg/m³ 0.05 mg/m³ 0.05 mg/m^3 Nickel, Metal (as Ni) 0.2 mg/m³ 1 mg/m³ 0.015 mg/m³

Personal protective equipment

Respiratory protection:

Suitable respiratory protection for higher concentrations or long-term effect: Particle filter EN 143 Type

P1, low efficiency, (solid particles of inert substances).

Hand protection:

Chemical resistant protective gloves (EN 374)

e.g. nitrile rubber (0.4 mm), chloroprene rubber (0.5 mm), polyvinylchloride (0.7 mm) and other

Manufacturer's directions for use should be observed because of great diversity of types.

Eve protection:

Safety glasses with side-shields (frame goggles) (EN 166)

General safety and hygiene measures:

Handle in accordance with good industrial hygiene and safety practice. Due to the colouring properties of the product closed work clothes should be used, to avoid stains during manipulation. Hands and/or face should be washed before breaks and at the end of the shift.

SECTION 9: Physical and chemical properties

Appearance/form Yellow/ powder Odor SPECIFIC GRAVITY 4.5 6.5 Melting point/freezing point >1000c Initial boiling point and boiling range NA Flash point NA Evaporation rate NA Flammability (solid, gas) none Upper/lower flammability limits NA Upper/lower explosive limits NA Vapor pressure NA Vapor density NA Relative density NA Solubility(ies) insoluble Partition coefficient: n-octanol/water NΑ Auto-ignition temperature NA Decomposition temperature NA Viscosity NA Explosive properties Oxidizing properties none

SECTION 10: Stability and reactivity

Chemical stability STABLE

Possibility of hazardous reactions WILL NOT OCCUR

Incompatible materials NONE

Hazardous decomposition products N/A

SECTION 11: Toxicological information

ORAL LD50 > 10000 mg/kg bw

INHALATION N/A SKIN N/A

NON IRRITATING TO THE SKIN NON IRRITATING TO THE EYES

THIS PIGMENT IS NOT LISTED IN THE NATIONAL TOXICOLOGY PROGRAM (NTP) REPORT ON CARCINOGENS.

IT IS NOT LISTED AS A POTENTIAL CARCINOGEN IN THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC) MONOGRAPHS.

IT IS NOT FOUND TO BE A CARCINOGEN BY THE OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION(OSHA)

SECTION 12: Ecological information

ECOTOXICITYNO DATADEGRADABILITYNO DATAMOBILITYNO DATABIOACCUMULATIVENO DATA

SECTION 13: Disposal considerations

Disposal of the product Contain spillage and scoop or vacuum. Avoid making dust

put in appropriate container for disposal. Waste disposal method in accordance with

Federal, State and Local Laws.

Disposal of contaminated packagingDispose of as unused product.

Waste treatment MUST BE PROCESSED THROUGH IN-HOUSE TREATMENT

Sewage disposal AVOID CITY DRAINS

SECTION 14: Transport information

 14.1 UN Number
 None

 14.2 UN Proper Shipping Name
 None

 14.3 Transport hazard class(es)
 None

 14.4 Packing group
 None

 14.5 Environmental hazards
 None

 14.6 Special precautions for user
 None

 14.7 Transport in bulk according to Annex II of None MARPOL 73/78 and the IBC Code
 None

SECTION 15: Regulatory information

Attention all Retailers of Mason Stains

ALL retailers of this product are REQUIRED by law to supply their customers with a copy of material safety data sheet with initial purchase.

***SARA 313

This product contains certain oxides and compounds which are subject to reporting requirements of Superfund Amendment and Reauthorization Act (SARA) of 1986, Section 313 of the Emergency Planning and Community Right to Know Act and of 40 CRF, Part 372.

The information contained in this MSDS must be provided to every employee who is exposed to this product in any way. We recommend the user reads and understands the contents herein before using this material.

PLEASE KEEP ON FILE FOR FUTURE REFERENCE. DO NOT THROW AWAY! MSDS'S ARE REQUIRED FOR FIRST SHIPMENT, AND WILL BE SENT AGAIN WHEN REVISED UPON YOUR NEXT ORDER OF PRODUCT OR BY REQUEST.

Disclamer

SECTION 16: REFERENCE INFORMATION

CPMA CLASSIFICATION AND CHEMICAL DESCRIPTIONS OF THE COMPLEX INORGANIC COLOR PIGMENTS Fourth Edition - January 2013 Update

https://www.osha.gov/index.html

http://chem.sis.nlm.nih.gov/chemidplus

13th Report on Carcinogens on October 2, 2014. http://monographs.iarc.fr/ENG/Classification/index.php Ls

- 1